


Solid flooring 20mm



CONSTRUCTION



AVAILABLE COLLECTIONS

Collection	Chateau	Kolonial	Soft Tone	Harfa Vintage	Pelgrim	Karel IV
Surface structure	Sanded	Brushed	Slightly brushed	Irregularly cross-sawn, brushed	Specially filled and distressed	Handcrafted
Finish	Osmo PolyX + Osmo PolyX top-coating					ESCO oxidative oil
Single Strip						
Connection	T&G					
Bevel	2V, 4V optional					
Length	40% sqm 500-1650, 60% sqm 1700+ max. 2400 mm					
Size	Grading					
120	Original	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
	Superb/Elegance	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
150	Original	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
	Superb/Elegance	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
185	Original	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
	Superb/Elegance	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
	Karel IV					<input checked="" type="checkbox"/>
Herringbone						
Connection	T&G					
Bevel	4V, no bevel optional					
100/120x600	Original	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	
	Superb/Elegance	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	

TECHNICAL PROPERTIES

	Test method	Request	Result
Production standard & Conformity	EN 14342, EN 13488, EN 13629, EN 13226		Implemented
Moisture content	ČSN EN 13183-1		9 ±2%
Formaldehyde emission	ČSN EN 717-1	≤ 0,124mg/m3	E1
PCP (pentachlorophenol)	CEN/TR 14823	≤ 5 ppm	meets
Slip resistance sanded	CEN/TS 15676		Dry ≥ 69, Wet ≥ 26
Slip resistance brushed	CEN/TS 15676		Dry ≥ 69, Wet ≥ 29
Reaction to fire	ČSN EN 13501-1		Cfl-S1
Thermal resistance	ČSN EN ISO 10456		0,15 m2 · K/W
Thermal conductivity	ČSN EN ISO 10456		0,13 W/mK
Biological durability	ČSN EN 335-1, ČSN EN 335-2		Class 1
Underfloor heating			<input type="checkbox"/> Not recommended

Recommended usage

Well-managed forests

Suitable for interior use in all project sectors: residential-commercial-hospitality-retail. Actual warranty & maintenance instructions apply
 This product is made of PEFC certified wood

